



** CLEARANCE DIMENSION IS 8" FOR CONCRETE MOUNT CONFIGURATION
 *** OPTIONAL HOODS REQUIRE 10" & 17" SIDEROOM, 28" HEADROOM AND 34" OPERATOR PROTRUSION

TNR INDUSTRIAL DOORS INC.

SHOP DRAWING, MODEL HDC, LEFT HAND

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES	EXT. DETAIL: DOOR MOUNT OPERATOR & INERTIA BRAKE	
<input type="checkbox"/> - GUIDE MOUNTED WINDBAR	<input type="checkbox"/> - FUSED DISCONNECT	- SPEEDS UP TO 30 IPS OPEN, 12 IPS CLOSE	LIMITATIONS: [OW<=20' & OH<=20'] OR [20'<OW<=25' & OH<=15']	
<input type="checkbox"/> - JAMB MOUNTED WINDBAR	<input type="checkbox"/> - LOOP DETECTOR	- TIMER TO CLOSE (USER SELECT)	DATE DRN: MAY 12, 2006	REVISION: F - OCT. 10, 2015
<input type="checkbox"/> - GUIDE GUARDS	<input type="checkbox"/> - WIRELESS RECEIVER	- NEMA 4 CONTROL PANEL & LIMIT BOX	DRAWN BY: HOWARD MULRAIN	DRAWING No.: D-600-0033
<input type="checkbox"/> - *** EXTERIOR HOODS	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- DIRECT CONNECT INERTIA BRAKE (OPTIONAL FOR DOORS <= 20' 0" x 10' 0") (INCLUDED ON ALL DOORS > 20' 0" x 10' 0")	ELECTRICAL CRITERIA: PLC & FREQUENCY INVERTER DRIVE	
<input type="checkbox"/> - *** SAFETY CHAIN GUARDS	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- WIRELESS REVERSING EDGE	CONTROL PANEL NEMA/EEMAC 4 STD. OR _____	
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- THRU-BEAM PHOTOEYE	PRIMARY POWER SUPPLY: _____ Volts, 3 Phase, 60 Hertz	
<input type="checkbox"/> - ELECTRIC REVERSING EDGE	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP	OPERATOR CRITERIA: HG, HIGH EFFICIENCY HELICAL GEAR	
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- KNOCK-AWAY STYLE BOTTOM BAR	LIMIT BOX NEMA/EEMAC 4 STD. OR _____	
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> -	- NEWGEN GUIDE AND CURTAIN LOK SYSTEM	_____ HP, DOOR SPEED: OPEN UP TO@ _____ ips, CLOSE UP TO@ _____ ips	
<input type="checkbox"/> - OPTIONAL DIRECT CONNECT INERTIA BRAKE FOR DOORS <= 20' 0" x 10' 0")	<input type="checkbox"/> -	- PROGRAMMABLE CONTROLLER	END USER:	
<input type="checkbox"/> -	<input type="checkbox"/> -	- FREQUENCY INVERTER	DEALER:	
			DOOR SIZE:	SERIAL No.: TNR-