



\*\* CLEARANCE DIMENSION IS 8" FOR CONCRETE MOUNT CONFIGURATION  
 \*\*\* OPTIONAL HOODS REQUIRE 10" & 16 1/2" SIDEROOM, 32" HEADROOM AND 34" OPERATOR PROTRUSION

<b>TNR INDUSTRIAL DOORS INC.</b>	
<b>SHOP DRAWING, MODEL HDT, LEFT HAND</b>	
EXT. DETAIL: DOOR MOUNT OPERATOR & C'BAL SPRINGS	
LIMITATIONS: MAX. OPENING WIDTH 20', MAX. OPENING HEIGHT 20'	
DATE DR'N: DECEMBER 3, 2003	REVISION: G - OCT. 10, 2015
DRAWN BY: HOWARD MULRAIN	DRAWING No.: D-600-0003
ELECTRICAL CRITERIA:	
CONTROL PANEL NEMA/EEMAC 4 STD OR _____	
PRIMARY POWER SUPPLY: ___ Volts, 3 Phase, 60 Hertz	
OPERATOR CRITERIA: HG, HIGH EFFICIENCY HELICAL GEAR	
LIMIT BOX NEMA/EEMAC 4 STD. OR _____	
___ HP, DOOR SPEED: OPEN & CLOSE UP TO @ ___ ips	
END USER:	
DEALER:	
DOOR SIZE:	SERIAL No.: TNR

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - GUIDE MOUNTED WINDBAR	<input type="checkbox"/> - RELAY LOGIC CONTROLS	- SPEEDS UP TO 30 IPS
<input type="checkbox"/> - JAMB MOUNTED WINDBAR	<input type="checkbox"/> - RELAY LOGIC c/w TIMER TO CLOSE	- NEMA 4, WALL MOUNTED CONTROL PANEL
<input type="checkbox"/> - 200,000 CYCLE C'BAL SPRINGS	<input type="checkbox"/> - FUSED DISCONNECT	- NEMA 4 LIMIT BOX ON OPERATOR
<input type="checkbox"/> - GUIDE GUARDS	<input type="checkbox"/> - LOOP DETECTOR	- 100,000 CYCLE COUNTERBALANCE SPRINGS
<input type="checkbox"/> - *** EXTERIOR HOODS	<input type="checkbox"/> - WIRELESS RECEIVER	- WIRELESS REVERSING EDGE
<input type="checkbox"/> - *** SAFETY CHAIN GUARDS	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- THRU-BEAM PHOTOEYE
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP
<input type="checkbox"/> - ELECTRIC REVERSING EDGE	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- KNOCK-AWAY STYLE BOTTOM BAR
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- NEWGEN GUIDE AND CURTAIN LOK SYSTEM
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- PROGRAMMABLE CONTROLLER
<input type="checkbox"/> -	<input type="checkbox"/> -	- INTEGRATED TIMER TO CLOSE (ADJUSTABLE)
<input type="checkbox"/> -	<input type="checkbox"/> -	-